AmendReservationRequest

Parkonect Presales API · https://qa.flashparking.com/docs/amendreservationrequest/

Request:

Vehicles:

Response Object:

The following routes are available for this service:

POST, OPTIONS	**/ParkonectAPI/AmendReservation**

To override the Content-Type in your client's HTTP **Accept** Header, append the **.xml** suffix or **?format=xml**

HTTP + XML

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /xml/reply/AmendReservationRequest HTTP/1.1
Host: api.parkonect.com
Content-Type: application/xml
Content-Length: length

<AmendReservationRequest xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
  <commFee>0</commFee>
  <customerEmail>String</customerEmail>
  <customerName>String</customerName>
  <customerPhone>String</customerPhone>
  <garageId>0</garageId>
  <grossPrice>0</grossPrice>
  <netAmount>0</netAmount>
  <orderNumber>String</orderNumber>
  <passWord>String</passWord>
  <reentryAllowed>false</reentryAllowed>
  <userName>String</userName>
  <vehicles>
    <VehicleReservationInfo>
      <barcode>String</barcode>
      <endTime>0001-01-01T00:00:00</endTime>
      <licensePlate>String</licensePlate>
      <startTime>0001-01-01T00:00:00</startTime>
      <vehicleColor>String</vehicleColor>
      <vehicleMake>String</vehicleMake>
      <vehicleModel>String</vehicleModel>
    </VehicleReservationInfo>
  </vehicles>
  <vendorId>0</vendorId>
</AmendReservationRequest>
```

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: length

<AmendReservationResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
```

```
  <message>String</message>
  <orderNumber>String</orderNumber>
  <orderTime>String</orderTime>
  <reservations>
    <CheckReservationInfo>
      <barcode>String</barcode>
      <canceled>false</canceled>
      <canceledTime>String</canceledTime>
      <checkInTime>String</checkInTime>
      <checkOutTime>String</checkOutTime>
      <commFee>0</commFee>
      <customerEmail>String</customerEmail>
      <customerName>String</customerName>
      <customerPhone>String</customerPhone>
      <endTime>String</endTime>
      <garageId>0</garageId>
      <grossPrice>0</grossPrice>
      <licensePlate>String</licensePlate>
      <netAmount>0</netAmount>
      <orderNumber>String</orderNumber>
      <reentryAllowed>false</reentryAllowed>
      <startTime>String</startTime>
      <used>false</used>
      <vehicleColor>String</vehicleColor>
      <vehicleMake>String</vehicleMake>
      <vehicleModel>String</vehicleModel>
      <vendorId>0</vendorId>
    </CheckReservationInfo>
  </reservations>
  <success>false</success>
</AmendReservationResponse>
```

The following routes are available for this service:

POST, OPTIONS	**/ParkonectAPI/AmendReservation**	

To override the Content-type in your client's HTTP **Accept** Header, append the **.json** suffix or **?format=json**

To embed the response in a **JSONP** callback, append **?callback=myCallback**

HTTP + JSON

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /json/reply/AmendReservationRequest HTTP/1.1
Host: api.parkonect.com
Content-Type: application/json
Content-Length: length

{
  "vendorId": 0,
  "userName": "String",
  "passWord": "String",
  "garageId": 0,
  "orderNumber": "String",
  "vehicles": [
    {
      "barcode": "String",
      "licensePlate": "String",
      "vehicleMake": "String",
      "vehicleModel": "String",
      "vehicleColor": "String",
      "startTime": "\/Date(-62135596800000-0000)\/",
      "endTime": "\/Date(-62135596800000-0000)\/"
    }
  ],
  "grossPrice": 0,
  "commFee": 0,
  "netAmount": 0,
  "customerName": "String",
```

```
  "customerEmail": "String",
  "customerPhone": "String",
  "reentryAllowed": false
}
```

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: length

{
  "success": false,
  "message": "String",
  "orderTime": "String",
  "orderNumber": "String",
  "reservations": [
    {
      "vendorId": 0,
      "garageId": 0,
      "barcode": "String",
      "licensePlate": "String",
      "orderNumber": "String",
      "used": false,
      "canceled": false,
      "startTime": "String",
      "endTime": "String",
      "canceledTime": "String",
      "checkInTime": "String",
      "checkOutTime": "String",
      "grossPrice": 0,
      "commFee": 0,
      "netAmount": 0,
      "customerName": "String",
      "customerEmail": "String",
      "customerPhone": "String",
      "vehicleMake": "String",
      "vehicleModel": "String",
      "vehicleColor": "String",
      "reentryAllowed": false
    }
```

```
  ]
}
```

The following routes are available for this service:

POST, OPTIONS	**/ParkonectAPI/AmendReservation**	

To override the Content-Type in your client's HTTP **Accept** Header, append the **.jsv** suffix or **?format=jsv**

HTTP + JSV

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values

```
POST /jsv/reply/AmendReservationRequest HTTP/1.1
Host: api.parkonect.com
Content-Type: text/jsv
Content-Length: length

{
□vendorId: 0,
□userName: String,
□passWord: String,
□garageId: 0,
□orderNumber: String,
□vehicles:
□[
□□{
□□□barcode: String,
□□□licensePlate: String,
□□□vehicleMake: String,
```

```
    vehicleModel: String,
    vehicleColor: String,
    startTime: 0001-01-01,
    endTime: 0001-01-01
  }
 ],
 grossPrice: 0,
 commFee: 0,
 netAmount: 0,
 customerName: String,
 customerEmail: String,
 customerPhone: String,
 reentryAllowed: False
}
```

```
HTTP/1.1 200 OK
Content-Type: text/jsv
Content-Length: length

{
 success: False,
 message: String,
 orderTime: String,
 orderNumber: String,
 reservations:
 [
  {
    vendorId: 0,
    garageId: 0,
    barcode: String,
    licensePlate: String,
    orderNumber: String,
    used: False,
    canceled: False,
    startTime: String,
    endTime: String,
    canceledTime: String,
    checkInTime: String,
    checkOutTime: String,
```

```
□□□grossPrice: 0,
□□□commFee: 0,
□□□netAmount: 0,
□□□customerName: String,
□□□customerEmail: String,
□□□customerPhone: String,
□□□vehicleMake: String,
□□□vehicleModel: String,
□□□vehicleColor: String,
□□□reentryAllowed: False
□□}
□]
}
```

The following routes are available for this service:

POST, OPTIONS	**/ParkonectAPI/AmendReservation**	

To override the Content-Type in your client's HTTP **Accept** Header, append the **.csv** suffix or **?format=csv**

HTTP + CSV

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /csv/reply/AmendReservationRequest HTTP/1.1
Host: api.parkonect.com
Content-Type: text/csv
Content-Length: length

vendorId,userName,passWord,garageId,orderNumber,vehicles,grossPrice,commFee,netAmount,customerName
```

```
,customerEmail,customerPhone,reentryAllowed
0,String,String,0,String,"[{barcode:String,licensePlate:String,vehicleMake:String,vehicleModel:Str
ing,vehicleColor:String,startTime:0001-01-01,endTime:0001-01-
01}]",0,0,0,String,String,String,False
```

```
HTTP/1.1 200 OK
Content-Type: text/csv
Content-Length: length

success,message,orderTime,orderNumber,reservations
False,String,String,String,"[{vendorId:0,garageId:0,barcode:String,licensePlate:String,orderNumber
:String,used:False,canceled:False,startTime:String,endTime:String,canceledTime:String,checkInTime:
String,checkOutTime:String,grossPrice:0,commFee:0,netAmount:0,customerName:String,customerEmail:St
ring,customerPhone:String,vehicleMake:String,vehicleModel:String,vehicleColor:String,reentryAllowe
d:False}]"
```

To override the Content-Type in your client's HTTP **Accept** Header, append the **.soap11** suffix or **?format=soap11**

HTTP + SOAP11

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /soap11 HTTP/1.1
Host: api.parkonect.com
Content-Type: text/xml; charset=utf-8
Content-Length: length
SOAPAction: AmendReservationRequest

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
```

```
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <AmendReservationRequest xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
      <commFee>0</commFee>
      <customerEmail>String</customerEmail>
      <customerName>String</customerName>
      <customerPhone>String</customerPhone>
      <garageId>0</garageId>
      <grossPrice>0</grossPrice>
      <netAmount>0</netAmount>
      <orderNumber>String</orderNumber>
      <passWord>String</passWord>
      <reentryAllowed>false</reentryAllowed>
      <userName>String</userName>
      <vehicles>
        <VehicleReservationInfo>
          <barcode>String</barcode>
          <endTime>0001-01-01T00:00:00</endTime>
          <licensePlate>String</licensePlate>
          <startTime>0001-01-01T00:00:00</startTime>
          <vehicleColor>String</vehicleColor>
          <vehicleMake>String</vehicleMake>
          <vehicleModel>String</vehicleModel>
        </VehicleReservationInfo>
      </vehicles>
      <vendorId>0</vendorId>
    </AmendReservationRequest>
  </soap:Body>
</soap:Envelope>
```

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: length

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
```

```
  <soap:Body>
    <AmendReservationResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
      <message>String</message>
      <orderNumber>String</orderNumber>
      <orderTime>String</orderTime>
      <reservations>
        <CheckReservationInfo>
          <barcode>String</barcode>
          <canceled>false</canceled>
          <canceledTime>String</canceledTime>
          <checkInTime>String</checkInTime>
          <checkOutTime>String</checkOutTime>
          <commFee>0</commFee>
          <customerEmail>String</customerEmail>
          <customerName>String</customerName>
          <customerPhone>String</customerPhone>
          <endTime>String</endTime>
          <garageId>0</garageId>
          <grossPrice>0</grossPrice>
          <licensePlate>String</licensePlate>
          <netAmount>0</netAmount>
          <orderNumber>String</orderNumber>
          <reentryAllowed>false</reentryAllowed>
          <startTime>String</startTime>
          <used>false</used>
          <vehicleColor>String</vehicleColor>
          <vehicleMake>String</vehicleMake>
          <vehicleModel>String</vehicleModel>
          <vendorId>0</vendorId>
        </CheckReservationInfo>
      </reservations>
      <success>false</success>
    </AmendReservationResponse>
  </soap:Body>
</soap:Envelope>
```

To override the Content-type in your client's HTTP **Accept** Header, append the **.soap12** suffix or **?format=soap12**

HTTP + SOAP12

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /soap12 HTTP/1.1
Host: api.parkonect.com
Content-Type: text/xml; charset=utf-8
Content-Length: length

<?xml version="1.0" encoding="utf-8"?>
<soap12:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:soap12="http://www.w3.org/2003/05/soap-
envelope">
  <soap12:Body>
    <AmendReservationRequest xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
      <commFee>0</commFee>
      <customerEmail>String</customerEmail>
      <customerName>String</customerName>
      <customerPhone>String</customerPhone>
      <garageId>0</garageId>
      <grossPrice>0</grossPrice>
      <netAmount>0</netAmount>
      <orderNumber>String</orderNumber>
      <passWord>String</passWord>
      <reentryAllowed>false</reentryAllowed>
      <userName>String</userName>
      <vehicles>
        <VehicleReservationInfo>
          <barcode>String</barcode>
          <endTime>0001-01-01T00:00:00</endTime>
          <licensePlate>String</licensePlate>
          <startTime>0001-01-01T00:00:00</startTime>
          <vehicleColor>String</vehicleColor>
          <vehicleMake>String</vehicleMake>
```

```
          <vehicleModel>String</vehicleModel>
        </VehicleReservationInfo>
      </vehicles>
      <vendorId>0</vendorId>
    </AmendReservationRequest>
  </soap12:Body>
</soap12:Envelope>
```

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: length

<?xml version="1.0" encoding="utf-8"?>
<soap12:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:soap12="http://www.w3.org/2003/05/soap-
envelope">
  <soap12:Body>
    <AmendReservationResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
      <message>String</message>
      <orderNumber>String</orderNumber>
      <orderTime>String</orderTime>
      <reservations>
        <CheckReservationInfo>
          <barcode>String</barcode>
          <canceled>false</canceled>
          <canceledTime>String</canceledTime>
          <checkInTime>String</checkInTime>
          <checkOutTime>String</checkOutTime>
          <commFee>0</commFee>
          <customerEmail>String</customerEmail>
          <customerName>String</customerName>
          <customerPhone>String</customerPhone>
          <endTime>String</endTime>
          <garageId>0</garageId>
          <grossPrice>0</grossPrice>
          <licensePlate>String</licensePlate>
          <netAmount>0</netAmount>
          <orderNumber>String</orderNumber>
```

```
          <reentryAllowed>false</reentryAllowed>
          <startTime>String</startTime>
          <used>false</used>
          <vehicleColor>String</vehicleColor>
          <vehicleMake>String</vehicleMake>
          <vehicleModel>String</vehicleModel>
          <vendorId>0</vendorId>
        </CheckReservationInfo>
      </reservations>
      <success>false</success>
    </AmendReservationResponse>
  </soap12:Body>
</soap12:Envelope>
```