OnDemandLogoutRequest

Parkonect Presales API · https://qa.flashparking.com/docs/ondemandlogoutrequest/

Field Name	Data Type	Description
garageId	int	The garage ID
orderNumber	string	The order number
passWord	string	Password
userName	string	Username
vendorId	int	The vendor ID

Field	Description
message	A message with clarifying information about the result is provided in this field
success	The request succeeded as intended

The following routes are available for this service:

POST, OPTIONS	**/ParkonectAPI/OnDemandLogout**

To override the Content-Type in your client's HTTP **Accept** Header, append the **.xml** suffix or **?format=xml**

HTTP + XML

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /xml/reply/OnDemandLogoutRequest HTTP/1.1
Host: api.parkonect.com
Content-Type: application/xml
Content-Length: length

<OnDemandLogoutRequest xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
    <garageId>0</garageId>
    <orderNumber>String</orderNumber>
    <passWord>String</passWord>
    <userName>String</userName>
    <vendorId>0</vendorId>
</OnDemandLogoutRequest>
```

```
HTTP
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: length

<OnDemandLogoutResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
    <message>String</message>
    <success>false</success>
</OnDemandLogoutResponse>
```

The following routes are available for this service:

POST, OPTIONS	**/ParkonectAPI/OnDemandLogout**

To override the Content-type in your client's HTTP **Accept** Header, append the **.json** suffix or **?format=json**

To embed the response in a **JSONP** callback, append **?callback=myCallback**

HTTP + JSON

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /json/reply/OnDemandLogoutRequest HTTP/1.1
Host: api.parkonect.com
Content-Type: application/json
Content-Length: length

{"vendorId":0,"garageId":0,"userName":"String","passWord":"String","orderNumber":"String"}
```

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: length

{"success":false,"message":"String"}
```

The following routes are available for this service:

POST, OPTIONS	**/ParkonectAPI/OnDemandLogout**

To override the Content-type in your client's HTTP **Accept** Header, append the **.jsv** suffix or **?format=jsv**

HTTP + JSV

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /jsv/reply/OnDemandLogoutRequest HTTP/1.1
Host: api.parkonect.com
Content-Type: text/jsv
Content-Length: length
```

```
{
vendorId: 0,
garageId: 0,
userName: String,
passWord: String,
orderNumber: String
}
```

```
HTTP/1.1 200 OK
Content-Type: text/jsv
Content-Length: length

{
success: False,
message: String
}
```

The following routes are available for this service:

POST, OPTIONS	**/ParkonectAPI/OnDemandLogout**	

To override the Content-type in your client's HTTP **Accept** Header, append the **.csv** suffix or **?format=csv**

HTTP + CSV

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /csv/reply/OnDemandLogoutRequest HTTP/1.1
Host: api.parkonect.com
Content-Type: text/csv
Content-Length: length

vendorId,garageId,userName,passWord,orderNumber
```

```
0,0,String,String,String
```

```
HTTP/1.1 200 OK
Content-Type: text/csv
Content-Length: length

success,message
False,String
```

To override the Content-type in your client's HTTP **Accept** Header, append the **.soap11** suffix or **?format=soap11**

HTTP + SOAP11

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /soap11 HTTP/1.1
Host: api.parkonect.com
Content-Type: text/xml; charset=utf-8
Content-Length: length
SOAPAction: OnDemandLogoutRequest

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
    <soap:Body>

<OnDemandLogoutRequest xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
    <garageId>0</garageId>
    <orderNumber>String</orderNumber>
    <passWord>String</passWord>
    <userName>String</userName>
    <vendorId>0</vendorId>
```

```
</OnDemandLogoutRequest>

    </soap:Body>
</soap:Envelope>
```

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: length

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
    <soap:Body>

<OnDemandLogoutResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
    <message>String</message>
    <success>false</success>
</OnDemandLogoutResponse>

    </soap:Body>
</soap:Envelope>
```

To override the Content-type in your client's HTTP **Accept** Header, append the **.soap12** suffix or **?format=soap12**

HTTP + SOAP12

The following are sample HTTP requests and responses. The placeholders shown need to be replaced with actual values.

```
POST /soap12 HTTP/1.1
Host: api.parkonect.com
Content-Type: text/xml; charset=utf-8
Content-Length: length
```

```
<?xml version="1.0" encoding="utf-8"?>
<soap12:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:soap12="http://www.w3.org/2003/05/soap-
envelope">
    <soap12:Body>

<OnDemandLogoutRequest xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
    <garageId>0</garageId>
    <orderNumber>String</orderNumber>
    <passWord>String</passWord>
    <userName>String</userName>
    <vendorId>0</vendorId>
</OnDemandLogoutRequest>

    </soap12:Body>
</soap12:Envelope>
```

```
HTTP/1.1 200 OK
Content-Type: application/xml
Content-Length: length

<?xml version="1.0" encoding="utf-8"?>
<soap12:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:soap12="http://www.w3.org/2003/05/soap-
envelope">
    <soap12:Body>

<OnDemandLogoutResponse xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Parkonect.Client.Model">
    <message>String</message>
    <success>false</success>
</OnDemandLogoutResponse>

    </soap12:Body>
</soap12:Envelope>
```